

HABECO

Security Container

EN 1143-1 Grade III



- HABECO Security Containers have two standard models SC 6000 and SC 3000, both have certificate EN 1143-1, grade III.
- SC 6000 can be loaded directly on truck with the trucks hydraulic hook. SC 3000 can be loaded on a truck with forklift or crane.
- The Security Container can be used for transport of dangerous or valuable goods. But also as movable or stationary Vaultroom. The containers can as option have security alarm connected to GPS and mobile.

The construction can be changed without any notice.

| Model | Outside dim. H x W x L | Inside dim. H x W x L | Inside area m ² | Netto weight Kg | Total weight Kg |
|-----------|---------------------------|--------------------------|-------------------------------|-----------------|-----------------|
| S.C. 6000 | 2940 x 2560 x 6320 | 2240 x 2200 x 5660 | Ca 12,5 | 10.000 | 18.000 |
| S.C. 3000 | 2440 x 2445 x 2990 | 1950 x 2145 x 2530 | Ca 5,5 | 4.500 | 10.000 |

Security Container SC 6000 and SC 3000

INFORMATION

The Security Container is constructed to give very high protection against burglary and even fire resistance during some time, during transportation and storage at the same place.

The purpose is storage of products when high security is needed, like tools, dynamite, weapon or similar.

The Container is also suitable for transportation of dangerous or valuable goods.

SECURITY LEVEL

The security vault room, inside the container, is constructed to withstand attack according to European Norm EN 1143-1. Those type of products must be tested by accredited test institute.

The products can be tested against different grades of attacks. After the test the product will get a certificate which confirm approved test and grade.

Usually this type of products are tested after the grades 0-V. We have chosen to test our Security Container after grade III which gives good satisfaction against burglary attacks.

TECHNICAL DATA

| | SC 6000 | SC 3000 |
|---------------|-----------|-----------|
| Outside: High | 2,94 m | 2,44 m |
| Length | 6,32 m | 2,99 m |
| Width | 2,56 m | 2,44 m |
| Inside: High | 2,24 m | 1,95 m |
| Length | 5,66 m | 2,53 m |
| Width | 2,20 m | 2,14 m |
| Weight: | 10.000 kg | 4.500 kg |
| Max load: | 8.000 kg | 5.500 kg |
| Total weight: | 18.000 kg | 10.000 kg |

HANDLING OF SECURITY CONTAINER – PRODUCTS

Security Doors

When the Security Container is placed on the ground it must be in correct horizontal level. Otherwise it can be small difficulties to open and close the doors of the vault room. The doors shall not be subject for powerful strokes, if it happens, the security function in the doors can block the bolts.

In the right handed door it is installed a high security changeable key lock FÅS S&G 6890, class C in accordance to ENV 1300 and class 3, VDS. The lock is delivered with two keys.

If one of the key will be lost it is possible to buy new keys, you can choose how many you need.

The lock can be changed to fit the new keys.

If the doors during longer time are placed in a dusty/ dirty environment it is recommended to grease, at least once per year, the hinges and the locking system. Ask your supplier for service.

INCREASED SECURITY LEVEL

If you want you can increase the level of protection. When you order a Security Container it is possible to buy a system (alarm) with position alarm and different type of attack alarms.

- The position system gives you control about which place is the Security Container standing, all the time.
- Magnetic contact can be installed at the container doors (not at vault room) and gives alarm directly, if somebody open the container doors, to your mobile and 2 other mobiles if you don't answer.
- Plus other possibilities like siren, vibration sensors, fire sensors .